
NuTek® Plastic Switch & Outlet Boxes

NuTek® plastic boxes are available in a broad range of models to suit almost any application, and are designed to be energy efficient and very builder friendly. Fast and easy to install, they are a real time saver on any residential project for the professional electrician.

All NuTek® boxes are fully CSA-approved, exceeding the requirements for flammability and impact resistance.

Highest Quality Material

NuTek® boxes are made of a clean, lightweight plastic that's very easy to work with and effortless to carry around the jobsite. Molded from a high-strength resin, these boxes also provide the practical toughness and durability to perform in a wide range of temperature conditions, at both hot and cold extremes.

Environmentally Safe and Energy Efficient

NuTek® boxes are environmentally safe. All boxes are two-hour fire rated and, if involved in a fire, emit only non-corrosive gases.

NuTek®'s AIRTIGHT models are the perfect choice for use in R2000 homes. The AIRTIGHT models are made with a closed cell foam gasket around the drywall flange and cable entry tabs, to form an automatic 100% AIRTIGHT seal when installed. No additional vapor barrier is ever required.

Quick and Easy Cost Saving Installation


- 1- Large cubic capacity - In addition to having more finger room, NuTek® boxes can accommodate more wires/circuits and larger wiring devices (ie: dimmers, thermostats, GFI's).
- 2- Self-clamping cable entry tabs - No tools are required to tighten or loosen cable clamps in a NuTek® box.
- 3- External mounting flange - All boxes are pre-measured for ½" drywall, and can be rapidly installed with either nails or screws.
- 4- Internal screw bosses ensure a perfect straight line drywall cut on the outside of the box. This means no nicked or cut wires and the elimination of drywall patching. - The inside of the box and device screw holes will remain "mud" free.
- 5- Bottom mounted ground screw(s) allow all wires to be pushed back into the box during the "rough-in" stage of the job.

NuTek® Plastic Switch & Outlet Box Models

Single Gang Switch Box

Model **WSW**


- 18 cubic inch capacity
- Positioning tabs eliminate the need to measure for 1/2" drywall
- 4 hinged cable entry tabs
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 2.25" (W) x 2.75" (D)



Two Gang Switch Box

Model **2-WSW**


- 36 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- 8 hinged cable entry tabs
- Easy access to bottom-mounted ground screws
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 4" (W) x 2.75" (D)
Flange: 5" (H) x 5.5" (W)



Three Gang Switch Box

Model **3-WSW**

- 54 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- 12 hinged cable entry tabs
- Easy access to bottom-mounted ground screws
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 5.75" (W) x 2.75" (D)
Flange: 5" (H) x 7.5" (W)




NuTek® Plastic Switch & Outlet Box Models

Ceiling Box

Model **WOCT**

- 26 cubic inch capacity
- Positioning tabs eliminate the need to measure for 1/2" drywall
- 4 hinged cable entry tabs
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 4" (W) x 2.75" (D)



Single Gang Switch Box - armored cable/BX Model **WSWBX**

- 20 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Approved for armored (eg. AC90/BX) and nonmetallic sheathed cable
- External cable connectors installed on all boxes
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 2.25" (W) x 2.75" (D)
Flange: 5" (H) x 4.25" (W)



Range & Dryer Box - 4 11/16" Model **WRD**

Model **WRD**

- 65 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- 4 hinged cable entry tabs (approved for nonmetallic cable up to 8/3)
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 4 11/16" (H) x 4 11/16" (W) x 3" (D)
Flange: 6.9" (H) x 6.9" (W)



NuTek® Airtight Plastic Switch & Outlet Box Models

100% AIRTIGHT NO ADDITIONAL VAPOR BARRIER REQUIRED IMPROVES SOUNDPROOFING

Single Gang Switch Box

Model **F-WSW**

- 18 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Flange and 4 hinged cable entry tabs are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 2.25" (W) x 2.75" (D)
Flange: 5" (H) x 3.5" (W)



Two Gang Switch Box

Model **2-FWSW**


- 36 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Flange and 8 hinged cable entry tabs are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screws
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 4" (W) x 2.75" (D)
Flange: 5" (H) x 5.5" (W)



Three Gang Switch Box

Model **3-FWSW**

- 54 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Flange and 12 hinged cable entry tabs are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screws
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 5.75" (W) x 2.75" (D)
Flange: 5" (H) x 7.5" (W)



NuTek® Airtight Plastic Switch & Outlet Box Models

Ceiling Box

Model **F-WOCT**

- 26 cubic inch capacity
- Positioning flange eliminate the need to measure for 1/2" drywall
- Flange and 4 hinged cable entry tabs are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 3.8" (W) x 2.75" (D)
Flange Diameter: 5.25"



Single Gang Switch Box - armored cable/BX Model **FWSWBX**


- 20 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Approved for armored (eg. AC90/BX) and nonmetallic sheathed cable
- Flange and external cable/BX connectors are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 3.75" (H) x 2.25" (W) x 2.75" (D)
Flange: 5" (H) x 4.25" (W)



Range & Dryer Box - 4 11/16"

Model **F-WRD**

- 65 cubic inch capacity
- Positioning flange eliminates the need to measure for 1/2" drywall
- Flange and 4 hinged cable entry tabs (approved for nonmetallic cable up to 8/3) are covered with 100% airtight foam gasket
- Easy access to bottom-mounted ground screw
- Internal screw bosses for all devices
- 2-hour fire rated
- Dimensions: Box: 4 11/16" (H) x 4 11/16" (W) x 3" (D)
Flange: 6.9" (H) x 6.9" (W)



Extension Rings

Add 1/8", 1/2" or 5/8" to box depth of all single gang models for different thicknesses of drywall, wallboard or other finished materials.

Model WXT18


1/8" extension ring

Model WXT12

1/2" extension ring

Model WXT58

5/8" extension ring



Vapor Barriers

Made from high-strength polyethylene to resist cracking in cold temperatures. Designed to fit snugly on boxes for quicker cable entry and sealing (taping or caulking) of entrance holes. Vapor barriers can be externally mounted using screws or nails. Vapor barriers are not required when NuTek® airtight boxes are installed.

Model WSW-VB

Soft boot for WSW

Model WSW-VBR

Rigid boot for WSW

Model WOCT-VB

Soft boot for WOCT & 2-WSW

Model WOCT-VBR

Rigid boot for WOCT & 2-WSW

