



LG Industrial Systems

www.lgis.com

T-solution
Leader in Electrics & Automation

ISO 9001, ISO 14001

KSA



KSA



LG LOW VOLTAGE AIR CIRCUIT BREAKERS

LG Low Voltage
Air Circuit Breakers

LBA-A Type



LG
LOW VOLTAGE
AIR CIRCUIT
BREAKERS



1600A, 500V, 65kA



REPORT OF PERFORMANCE NUMBER: 96076-A

CLIENT: LG INDUSTRIAL SYSTEMS CO., LTD, KOREA
EQUIPMENT TESTED: TYPE LBA-18 LOW VOLTAGE AIR CIRCUIT BREAKER

MANUFACTURER'S RATINGS:

Voltage:	500 Vac
Continuous Current:	1600 A
Short-Circuit Current:	65 kA rms sym
Frequency:	60 Hz
Number of Phases:	3

DATES OF TEST: May 7, 1996

TESTED FOR: Rated Ultimate Short-Circuit Breaking Capacity

APPLICABLE TEST STANDARD(S): IEC 947-2, Test Sequence III

The tests have been carried out in accordance with the client's instructions. The test procedure and parameters were based on the above standard(s).

This report consists of 21 pages, and contains the results of tests performed at the KEMA-Powertest Laboratory on the above noted equipment. Publication or reproduction of the contents of this report in any form other than a complete copy is not permitted without written approval of KEMA-Powertest.

Measurement uncertainty can be verified by reviewing the instrument calibration records. The instruments used are calibrated on a regular basis and are traceable to the National Institute of Standards and Technology.

The results apply only to the specific devices tested and are recorded on the enclosed tables, oscillograms, photographs, etc. A table of contents is included on Page 2.



Harold L. Hess
Vice President

June 27, 1996
Date

Form: RFP-2-96

KEMA-Powertest, Inc. • 4378 County Line Road •

3150A, 500V, 85kA



REPORT OF PERFORMANCE NUMBER: 96083-A

CLIENT: LG INDUSTRIAL SYSTEMS CO., LTD, KOREA
EQUIPMENT TESTED: TYPE LBA-32 LOW VOLTAGE AIR CIRCUIT BREAKER

MANUFACTURER'S RATINGS:

Voltage:	500 Vac
Continuous Current:	3150 A
Short-Circuit Current:	85 kA rms sym
Frequency:	60 Hz
Number of Phases:	3

DATES OF TEST: May 7, 1996

TESTED FOR: Rated Ultimate Short-Circuit Breaking Capacity

APPLICABLE TEST STANDARD(S): IEC 947-2, Test Sequence III

The tests have been carried out in accordance with the client's instructions. The test procedure and parameters were based on the above standard(s).

This report consists of 20 pages, and contains the results of tests performed at the KEMA-Powertest Laboratory on the above noted equipment. Publication or reproduction of the contents of this report in any form other than a complete copy is not permitted without written approval of KEMA-Powertest.

Measurement uncertainty can be verified by reviewing the instrument calibration records. The instruments used are calibrated on a regular basis and are traceable to the National Institute of Standards and Technology.

The results apply only to the specific devices tested and are recorded on the enclosed tables, oscillograms, photographs, etc. A table of contents is included on Page 2.



Harold L. Hess
Vice President

June 27, 1996
Date

Form: RFP-2-96

KEMA-Powertest, Inc. • 4378 County Line Road •

According to IEC 947-2
Passed the KEMA Test

Features LBA-A Type has the following features.

The terminal of the control circuit on the front enables easy handling.

Optimized design for efficient panel board.

- Two standardized heights and depths for each type (fixed type and draw-out type.)
- Four standardized external dimensions
(630, 800, 1000, 1250, 1600AF/2000, 2500AF/3200AF/4000,5000AF).
- Light weight contributes to easy installation into the board.

Standard Ampere Frame & Poles.

- 630AF, 800AF, 1000AF, 1250AF, 1600AF, 2000AF, 2500AF, 3200AF, 4000AF, 5000AF.
- Every type is available as 3 -pole or 4-pole.

Standard manual connection. (Auto connection optional)


Easy and safe handling of draw-out type with rail.

Variety of accessories (refer to page 10).

Economic product containing a large element of customer inputs right from the design stage.



Type Selection




* For further information refer to page 22, 23

Ratings


Type		LBA-06A	LBA-08A	LBA-10A	LBA-13A	LBA-16A	LBA-20A	LBA-25A	LBA-32A	LBA-40A	LBA-50A
Frame Current (A)		630	800	1,000	1,250	1,600	2,000	2,500	3,200	4,000	5,000
Rated Insulation Voltage (V)		660	660	660	660	660	660	660	660	660	660
Rated Operation Voltage (V)		660	660	660	660	660	660	660	660	660	660
Number of Poles		3 4	3 4	3 4	3 4	3 4	3 4	3 4	3 4	3 4	3 4
Rated Current of Trip Relay (A)		630-504-378		1000-800-600	1250-1000-750	1600-1280-960			3200-2500-1920		
		315-252-189	800-640-480	500-400-300	630-504-378	1000-800-600	2000-1600-1200	2500-2000-1500	2000-1600-1200	4000-3200-2400	5000-4000-3000
		126-101-76		200-160-120	500-400-300	500-400-300			1000-800-600	2000-1600-1200	
Rated Current of Neutral Pole(A)		630	800	1,000	1,250	1,600	1,600	1,600	1,600	2,500	2,500
Rated Short-Circuit Breaking Capacity (kA r.m.s., Symmetrical)/ Making Capacity (kA peak values) P-2(O-CO-CO)	IEC	AC660V	30/63	30/63	30/63	42/88.2	42/88.2	42/88.2	50/105	65/143	65/143
	BS	AC600V	42/88.2	42/88.2	42/88.2	50/105	50/105	50/105	65/143	85/187	85/187
	VDE	AC500V	50/105	50/105	50/105	50/105	65/143	65/143	85/187	100/220	100/220
	NEMA	AC600V	42/96.6	42/96.6	42/96.6	50/115	50/115	50/115	65/149.5	85/195.5	85/195.5
	ANSI	AC480V	50/115	50/115	50/115	65/149.5	65/149.5	65/149.5	85/195.5	100/230	100/230
	KS	AC550V	42/88.2	42/88.2	42/88.2	50/105	50/105	50/105	65/143	85/195.5	85/195.5
	JEC	AC460V	50/105	50/105	50/105	65/143	65/143	65/143	85/195.5	100/230	100/230
	LR	AC660V	30/63	30/63	30/63	48/88.2	42/88.2	42/88.2	50/105	-	-
		AC600V	42/88.2	42/88.2	42/88.2	50/105	50/105	50/105	65/143	88.1/211	88.1/211
		AC500V	50/105	50/105	50/105	65/143	65/143	65/143	85/195.5	105/256	105/256
	KR	AC500V	50/105	50/105	50/105	63/138.6	63/138.6	63/138.6	80/176	100/251	100/251
Rated Short Time Current (kA/1s)		42	42	42	50	50	50	50	65	85	85
Total Breaking Time (s)		0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.05	0.05
Closing Time (s)		0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.08	0.08
Number of operating cycles	Current conductive	3,000	3,000	3,000	3,000	3,000	3,000	3,000	2,000	1,000	1,000
	Current not conductive	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000	10,000

Exterior Dimensions (mm)

Fixed type



Draw-out type



Type	Fixed Type								Draw-out Type							
	3Pole				4Pole				3Pole				4Pole			
	a	b	c	d	a	b	c	d	a	b	c	d	a	b	c	d
LBA-06A																
LBA-08A																
LBA-10A	295				380				343				428			
LBA-13A																
LBA-16A		424	374	35		424	374	35		459	472	35		459	472	35
LBA-20A	430				515				478				563			
LBA-25A	536				621				584				669			
LBA-32A																
LBA-40A	687			85	817			85	742	521	528	80	872	521	528	80
LBA-50A																

Design features & Structure

Fixed Type


- ① Trip relay part
- ② Charge handle
- ③ "Open" button
- ④ "Close" "Open" indicator
- ⑤ "Close" button
- ⑥ "Charge" indicator



Draw-out Type

- ① Arc chamber
- ② Auto connection contacts
- ③ Draw-out rail

- ① Trip relay device
- ② Arc contact(moving)
- ③ Arc contact(fixed)
- ④ Arc chamber
- ⑤ CT
- ⑥ Main connector
- ⑦ Main contact
- ⑧ Contact spring
- ⑨ Load connector
- ⑩ Moving conduct
- ⑪ Charging spring
- ⑫ Charging device
- ⑬ Link device
- ⑭ Trip device
- ⑮ Charging handle



Mounting Configurations

Select Fixed Type or Draw-out Type



Fixed Type

- Compact design
- Direct fixing construction
- Compact design reduces panel board size

Draw-out handle







Extension rail

Draw-out Type

- Easy maintenance and inspection
- The draw-out rail is stored in the cradle
- Safety shutter
- Position S/W indicates "Connected" "Test" "Disconnected" "Draw-out" Position
- Short-Circuit "b" Contact
– Keep the control circuit on by closing the "b" contact.

Positions of Draw-out Type

Connected Position		<ul style="list-style-type: none"> • Main circuit and control circuit are connected. (Manual connection) • Normal operation condition
Test Position		<ul style="list-style-type: none"> • Main circuit disconnected, control circuit connected. • Testing is possible with the panel door closed.
Disconnected Position		<ul style="list-style-type: none"> • Main circuit and control circuit are disconnected. (Manual disconnected) • Panel door can be closed.
Draw-out Position		<ul style="list-style-type: none"> • The breaker can be removed in this position. • The breaker can be removed from the cradle by use of the extension rails.

Operation

Select Manual Charging Type or Motor Charging Type

Manual Charging Type

For closing, first charge the spring by using the charging handle and then press the close button. For opening, an open button disconnects the circuit.

- If the closing spring is fully charged, the charge indicator indicates "CHARGED".

- The buttons lock automatically so that the open and close buttons can not be operated at the same time.
- Main contacts status of main circuit is indicated by 'CLOSE' or 'OPEN'.

Motor Charging Type

Closing is performed by a closing spring which is remotely controlled. Pressing the charges button activates a motor that automatically charges the closing spring, which then closes the breaker. Motor charging and electrical closing is permitted between 85% and 110% of the rated voltage.

- Manual charging operation can also be performed.
- With breaker closed, charging is possible by manual action, but motor charging of closing spring can not be performed.
- With the open button pressed, closing operation can not be performed (electrical and mechanical lock).
- Closing operation can not be performed when off-lock is being used (electrical and mechanical lock).
- Circuit to prevent pumping is included (electrical lock).
- Caution is required, because lower closing signal voltage may reset pumping prevention circuit.
- Closing operation should follow at least one second after completion of charge.



● Ratings of motor charging

Minimum operating : 300VA

Rated Voltage (V)		Inrush Current (A)	Continuous Current (A)	Charging Time (s)
AC 50/60Hz	100~110V	10.5	3	Max.3
	120V	11	3	
	200~220V	6	1.5	
	240V	7	1.5	
DC	100~125V	11	4	


Power Source	Resetting Voltage
AC	50%
DC	20%

● Ratings of closing coil

Rated Voltage (V)		Inrush Current (A)	Closing Time (ms)
AC 50 / 60Hz	100~110V	5.5	Max. 60 (Contact time)
	120V	5.5	
	200~220V	5	
	240V	5	
DC	100~125V	5	

Optional Accessories

Installation location can be accessed from the front for easy maintenance and inspection.



- ① Auxiliary Switch (AX)
- ② Shunt Tripping Device (SHT)
- ③ Open-Close Counter (CNT)
- ④ Lockout Coil (LC)
- ⑤ Auxiliary Switch (AX)
- ⑥ Undervoltage Tripping Device (UVT)
- ⑦ OCR Alarm Switch (AL)

The Trip Relay (OCR) Alarm Switch (AL)

OCR alarm switch is an accessory needed if over current trip relay is required. The OCR alarm switch (AL) electrically alarms when breaker is tripped by trip relay activation.

This is activated by long-delay, short-delay and instantaneous tripping. However, it is not activated by ground-fault tripping, open button, undervoltage and shunt tripping devices.

It is an instantaneous action (15ms), so that the alarm circuit needs a self-holding circuit.



● Alarm switch operating

Breaker Condition	"a"contact
* Tripped either by long-delay, short-delay or instantaneous tripping	On
* Tripped either by the OPEN button, SHT,UVT or ground-fault tripping	Off
Open	
Close	

Auxiliary Switch (AX)

The auxiliary switch, which is installed in the breaker, displays the status of the breaker, either 'CLOSED' or 'OPEN'.

- 3a3b is standard, maximum 4a4b.
- Special use (Maximum)
 - Motor charging type : 4a3b
 - Shunt trip device type : 3a4b
 - Both of the above types : 3a3b



Breaker condition	"a" Contact	"b" Contact
Close	On	Off
Open	Off	On

● Ratings of AX and AL contacts

Contact Ratings	AC			DC		
	Rated Voltage (V)	Current(A) Resistive load	Inductive load	Rated Voltage (V)	Current(A) Resistive load	Inductive load
	460	5	2.5	250	5	3
	250	10	10	125	10	6
	125	10	10	30	10	10

Counter(CNT)

The counter mechanically indicates the number of operations of the breaker, counting at each closing operation.



Optional Accessories

Undervoltage Tripping Device (UVT)


The undervoltage tripping device (UVT), with UVT coil, lock-out coil and voltage controller, is installed in the breaker to automatically trip if the control power voltage is dropped below the drop-out voltage.

The voltage controller controls the voltage supplied to UVT coil and lockout coil.

- Cooperative action is allowed, because UVT coil and lockout coil can be simultaneously picked up and dropped out.

Type	Instantaneous 0.5S Delay	UVT-S	
		UVT-05S	
Rated Voltage		Pick-up Voltage	Drop-out Voltage
AC 100V~120V		70V~80V	40V~60V
AC 200V~240V		140V~170V	80V~120V
AC 380V~460V		266V~323V	152V~228V

- Two options are available: 0.5 second delayed action or instantaneous action when the UVT control voltage falls below the drop-out voltage.
- The Drop-out voltage remains the same regardless of the frequency due to the conversion into DC.



Lockout Coil (LC)

Even when the UVT is activated, the Air Circuit Breaker, may instantaneously come into contact by the closing spring force. A lockout coil prevents this by anti-electrical and mechanical closing action if voltage is lower than the drop-out voltage.

- Pick-up voltage and drop-out voltage are controlled by voltage controller


- When UVT is specified, lockout coil is also included. It is possible to specify the lockout coil only.



Rated Voltage	Pick-up Voltage	Drop-out Voltage
AC 100~120V	70V~85V	40V~60V
AC 200~240V	140V~170V	80V~120V
AC 380~460V	266V~323V	152V~228V

Condenser Tripping Device (CTD)

This device enables breaker opening within a definite time by remote electrical operation, even when there is no control power supply. This device is combined with a SHT tripping device.



Type	CTD-100	CTD-200
Rated Input Voltage (V)	AC100/110	AC200/220
Rated Frequency (Hz)	50/60	50/60
Rated Charging Voltage (V)	145/145	280/310
Charging Time	5s (max)	5s (max)
Tripping Time Capacity	3m (min)	2m (min)
Applicable SHT Voltage (V)	DC 100/110	DC 200/220
Voltage Fluctuation	85~110%	85~110%

* CTD is installed outside of the Air Circuit Breaker.

Shunt Tripping Device (SHT)

The shunt tripping device (SHT) trips the breaker remotely by electric signal. The shunt tripping device utilizes auxiliary switch (1a) to prevent damage. Tripping is permitted between 70% and 110% of rat.



AC

Rated Voltage	Inrush Current Peak(A)	Operating Time(ms)
100~125	5.5	40
200~220	2.0	40
240	2.0	40

DC

Rated Voltage	Inrush Current Peak(A)	Operating Time (ms)
100~125	5	40

Trip Relay (OCR)

Solid-state trip device characteristics and combinations



Type

Combinations		LBA-06A	LBA-08A	LBA-10A	LBA-13A	LBA-16A	LBA-20A	LBA-25A	LBA-32A	LBA-40A	LBA-50A
S-A ST-A	L S I I	•	•	•	•	•	•	•	•	•	•
	L I	•	•	•	•	•	•	•	•	•	•
	S I	•	•	•	•	•	•	•	•	•	•
	I	•	•	•	•	•	•	•	•	•	•
SGT-A	L S I -G	•	•	•	•	•	•	•	•	•	•
	L I -G	•	•	•	•	•	•	•	•	•	•
	S I -G	•	•	•	•	•	•	•	•	•	•
	I -G	•	•	•	•	•	•	•	•	•	•

S-A Over current protection(standard)

ST-A Over current protection, Trip indicator(LED)

SGT-A Over current protection, Trip indicator(LED), Ground-fault protection

Note (L) Long time delay (S) Short time delay (I) Instantaneous (G) Ground-fault

Trip Indicator(T)

The trip indicator consists of the lamps which display trip state of the breaker (long-delay, short-delay, instantaneous and ground-fault trip). To reset the trip indicator, push the reset button on the front of the trip relay or cut the control power.

- Control power is needed (refer to the below chart)

● Feature of Trip Indicator



Ground-fault protection(G)

Take adequate precautions since the following conditions are present when the ground fault protection is needed.

- The OCR alarm switch will not operate when the ground fault protection is tripped. If needed, please use the indicator contact.
- The ground-fault protection and the shunt tripping device use the same control power.

● Control Power

Type	Control power supply (power consumption:2VA)	
	Ground-Fault Protection	Trip Indicator
S-A	-	-
ST-A	-	AC100-120V/200-240V, DC100-110V/125V
SGT-A	AC100-120V/200-240V, DC100-110V/125V	

Abundant Protections





1	Rated current	• Adjustable in 3 steps : 60, 80 or 100% of the frame current.
2	Ampere setting continuous	• The current which the solid-state trip device can carry continuously • Adjustable in 3 steps : 80, 90 or 100% of the rated current.
3	Long-delay pick-up current	105-120% of the ampere setting continuous.
4	Long-delay tripping time	100 seconds at 200% of the ampere setting continuous.
5	Short-delay pick-up current	Adjustable in 4 steps (LBA 06~32), 3steps(LBA40~50)of the rated current.
6	Short-delay tripping time	Adjustable in 3 steps: max., med., or min. Refer to the characteristics curve.
7	Instantaneous pick-up current	Adjustable in 4 steps of the rated current.
8	Ground-fault pick-up current	Adjustable in 4 steps (LBA06~32), 3steps(LBA40~50)of the rated current.
9	Ground-fault tripping time	Adjustable in 2 steps: 0.3 sec or 0.8 sec.



Type	Frame size(A)	Rated maximum current(A)	Rated current setting(A)			Ground-fault pick-up current setting(A)			
			60% × If	80% × If	100% × If	10% × If	20% × If	30% × If	50% × If
LBA-06A	630	630	378	504	630	63	126	189	315
		315	189	252	315	31.5	63	94.5	157.5
		126	75.6	100.8	126	12.6	25.2	37.8	63
LBA-08A	800	800	480	640	800	80	160	240	400
		1000	600	800	1000	100	200	300	500
LBA-10A	1000	500	300	400	500	50	100	150	250
		200	120	160	200	20	40	60	100
		1250	750	1000	1250	125	250	375	625
LBA-13A	1250	630	378	504	630	63	126	189	315
		500	300	400	500	50	100	150	250
		250	150	200	250	25	50	75	125
LBA-16A	1600	1600	960	1280	1600	160	320	480	800
		1000	600	800	1000	100	200	300	500
		500	300	400	500	50	100	150	250
LBA-20A	2000	2000	1200	1600	2000	200	400	600	1000
LBA-25A	2500	2500	1500	2000	2500	250	500	750	1250
LBA-32A	3200	3200	1920	2560	3200	320	640	960	1600
		3000	1800	2400	3000	300	600	900	1500
		2000	1200	1600	2000	200	400	600	1000
		1000	600	800	1000	100	200	300	500
LBA-40A	4000	4000	2400	3200	4000	-	800	1200	2000
		2000	1200	1600	2000	-	400	600	1000
LBA-50A	5000	5000	3000	4000	5000	-	1000	1500	2500

Characteristics of protection

Characteristics of over current protection





Characteristics of ground-fault protection



Control Circuit



S-A Type



Trip Relay

---	User's wiring	S1+ S2-	SHT control source terminal
- . -	Plant wiring	US+ US-	UVT short circuit terminal
—<	Junction	UL1+ UL2-	UVT control source terminal
□	Terminal	CC+	Closing control source terminal
SHT	Shunt tripping device	M1+	Charging control source terminal
UVT	Under voltage tripping device	M2+	Self-holding charging control source terminal
LC	Lockout coil	MC-	Common terminal for charging and closing
CC	Closing coil		
CH	Charge complete signal output terminal		

ST-A Type




Trip Relay

	User's wiring		UVT short circuit terminal
	Plant wiring		UVT control source terminal
	Junction		Closing control source terminal
	Terminal		Charging control source terminal
	Shunt tripping device		Self-holding charging control source terminal
	Under voltage tripping device		Common terminal for charging and closing
	Lockout coil		Trip indicator control source terminal
	Closing coil		Trip indicating common terminal
	Charge complete signal output terminal		Long time delay trip indicating terminal
	SHT control source terminals		Short time delay trip indicating terminal
			Instantaneous trip indicating terminal

Control Circuit

SGT-A Type




Trip Relay

- User's wiring
- · - Plant wiring
- ⚡ Junction
- Terminal signal
- (SHT) Shunt tripping device
- (UVT) Under voltage tripping device
- (LC) Lockout coil
- (CC) Closing coil
- (CH) Charge complete signal output terminal
- (G1-) Ground fault indicating terminal
- (S3+) UVT short circuit terminal for ground fault trip


- [S1+] [S2-] SHT control source terminal
- [UL1+] [UL2-] UVT control source terminal
- [CC+] Closing control source terminal
- [M1+] Charging control source terminal
- [M2+] Self-holding charging control source terminal
- [M3-] Self-holding charging control source terminal
- [MC-] Common terminal for charging source terminal
- [R1+] [R2-] [R3-] Trip indicator control source terminal
- [E+] Trip indicating common terminal
- [E1-] Long time delay trip indicating terminal
- [E2-] Short time delay trip indicating terminal
- [E3-] Instantaneous trip indicating terminal

External Dimensions (LBA-06, 08, 10, 13, 16A)


Fixed Type



Draw -out Type




Installation Dimensions




* () 4 pole dimensions

External Dimensions (LBA-20, 25A)


Fixed Type



Draw-out Type




Installation Dimensions




* () 4 pole dimensions

External Dimensions (LBA-32A)


Fixed Type



Draw-out Type



Installation Dimensions




* () 4 pole dimensions


External Dimensions

(LBA-40, 50A)


Fixed Type



Front view




Side view




Rear view


Draw-out Type



Front view




Side view



Rear view


* () 4 pole dimensions

Installation Dimensions




Rear view(Fixed type)

Rear view(Draw-out type)




Bottom view(Fixed type)

Bottom view(Draw-out type)



Terminal(Fixed type)




Terminal(Draw-out type)

Arc insulation space

When braking the short circuit current, ionized gas evacuates from the arc extinguish chamber.

In order to allow the gas to evacuate insulation space should be reserved.

Type		LBA-06/08 / 10/13/16 / 20/25A	LBA-32A	LBA-40/50A
Fixed Type	A1	150	150	200
	A2	200	300	300
	B	100	100	100
	C	320	320	320
Draw-out Type	A1	100	150	200
	A2	200	300	300
	B	100	100	100
	C	418	418	474



Ordering Information

Circuit breaker			
Rating	V/ _____ Hz/ _____ AF _____	Number of poles	<input type="checkbox"/> 3P <input type="checkbox"/> 4P
Mounting configuration	<input type="checkbox"/> P(Fixed type) <input type="checkbox"/> E(with E class cradle) <input type="checkbox"/> F (with F ₂ class and safety shutter)		
Control circuit connection	<input type="checkbox"/> Housing type(standard) <input type="checkbox"/> Auto connection type		

Control unit			
TYPE	<input type="checkbox"/> E(Not needed) <input type="checkbox"/> S(standard) * Standard type (combination of L,S,I) <input type="checkbox"/> ST (standard, trip indicator) * L (Long time delay), S (Short time delay), <input type="checkbox"/> SGT (standard, trip indicator, ground-fault protection) I (Instantaneous)		
Control power	S,ST type <input type="checkbox"/> AC 100~120V <input type="checkbox"/> AC 200~240V <input type="checkbox"/> DC 100~120V <input type="checkbox"/> DC 125V SGT type <input type="checkbox"/> AC 100~120V <input type="checkbox"/> AC 200~240V <input type="checkbox"/> DC 100~110V <input type="checkbox"/> DC 125V		

Operation & accessories			
Operating mechanism	<input type="checkbox"/> manual charge <input type="checkbox"/> motor charge		
Rating of motor charging and closing coil (50/60Hz)	<input type="checkbox"/> AC 100~110V <input type="checkbox"/> AC 120V <input type="checkbox"/> AC 200~220V <input type="checkbox"/> AC 240V <input type="checkbox"/> DC 100~125V		
Under voltage trip device(UVT)	<input type="checkbox"/> Not needed <input type="checkbox"/> UVT-S <input type="checkbox"/> UVT-05S <input type="checkbox"/> AC 100~120V <input type="checkbox"/> AC 200~240V <input type="checkbox"/> AC 380~460V		
Shunt trip device(SHT)	<input type="checkbox"/> AC 100~125V <input type="checkbox"/> AC 200~220V <input type="checkbox"/> AC 240V <input type="checkbox"/> DC 100~125V		
Condenser trip device(CTD)	<input type="checkbox"/> CTD-100 <input type="checkbox"/> CTD-200		
Alarm s/w (AL)	<input type="checkbox"/> Not needed <input type="checkbox"/> Needed		
Auxiliary s/w (AX)	<input type="checkbox"/> 3a3b (standard) <input type="checkbox"/> 3a4b * Maximum number of AX : <input type="checkbox"/> 4a3b <input type="checkbox"/> 4a4b • Motor charging type : 4a3b • Shunt trip device : 3a4b • Motor charging + Shunt trip device : 3a3b		
Trip s/w (TS)	<input type="checkbox"/> Not needed <input type="checkbox"/> Needed		
Safety shutter(SS)	<input type="checkbox"/> Not needed <input type="checkbox"/> Needed		
Short circuit "b" contact	<input type="checkbox"/> Not needed <input type="checkbox"/> Needed (ea)		
Cell s/w (CL)	<input type="checkbox"/> Not needed <input type="checkbox"/> CL-C (ea), CL-D (ea)		

Mechanical and installation accessories			
Counter (CNT)	<input type="checkbox"/> Not needed <input type="checkbox"/> Needed		
Lockout coil(LC)	<input type="checkbox"/> AC 100~120V <input type="checkbox"/> AC 200~240V <input type="checkbox"/> AC 380~460V		

※ When ordering, please send us this sheet together.

Specifications

Ratings

Model	LBA-06A		LBA-10A		LBA-10A		LBA-13A		LBA-16A		LBA-20A		LBA-25A		LBA-32A		LBA-40A		LBA-50A	
Number of poles	3	4	3	4	3	4	3	4	3	4	3	4	3	4	3	4	3	4	3	4
Rated current (OCR)	630-504-378		810-640-480		100-800-600		1250-1000-750		1600-1280-960		2000-1600-1200		2500-2000-1500		3200-2500-1920		4000-3200-2400 2000-1600-1200		5000-3000-3000	
	315-252-189				500-400-300		630-504-378		1000-800-600						2000-1600-1200					
	126-101-76				200-160-120		500-400-300		500-400-300						1000-800-600					
Standard	IES 947-2, BS 4752, NEMA SG 3, VDE 0660, JEC 160																			

Mounting configuration

Fixed type and draw out type (Manual connection type is standard)

Closing method

Manual charging type and motor charging type (select the control voltage)

Accessories

Accessories	Undervoltage tripping device (UVT)	Shunt tripping device (SHT)	Condenser tripping device (CTD)	Auxiliary switch (AX)	Trip switch (TS)	OCR alarm switch (AL)	Open close counter (CNT)
Maximum number	1	1	1	4a4b	1a	1a	1

The economical type of auxiliary switches are 3a3b, Shunt tripping device is also attached.
If selecting 4a4b as an auxiliary, refer to page 9 of auxiliary switches.

Trip relay(OCR)

Not applicable to economy type

Type	S-A	Standard type (Overcurrent trip characteristics)
	ST-A	Standard + Trip indicator (LED)
	SGT-A	Standard + Trip indicator (LED) + Ground-fault protection

Default setting value of the OCR.

Trip relay unit

Type	LBA-06/08/10/13/16/20/25/32A	LBA-40/50A
Continuous conductive current	100% of rated current specified. 100second trip at 200%	
Short-delay tripping time	Pick up at 400% of the rated current	Pick up at 200%
Instantaneous pick-up current	Pick up at 1,600% of the rated current	Pick up at 1000%
Ground-fault protection	Pick up at 50% of the rated current. 0.8 second trip.	



LG Industrial Systems

■ HEAD OFFICE

LG TWIN TOWERS, 20 Yoido-dong, Youngdungpo-gu,
Seoul, 150-721, Korea
Tel. (82-2)3777-4870
Fax. (82-2)3777-4713
<http://www.lgis.com>

Global network

■ Dalian LG Industrial Systems Co.,Ltd China

● Address : No. 15 Liaohexi 3 Road, economic and technical development zone, Dalian, China
● Tel : 86-411-731-8210 ● Fax : 86-411-730-7560
● e-mail : lgisppm@mail.dlptt.ln.cn

■ LG-VINA Industrial Systems Co.,Ltd Vietnam

● Address : LGIS VINA Congty che tao may dien Viet-Hung Dong Anh Hanoi, Vietnam
● Tel : 84-4-882-0222 ● Fax : 84-4-882-0220
● e-mail : lgis-youn@hn.vnn.vn

■ LG Industrial Trading (Shanghai) Co.,Ltd China

● Address : Room1705-1707, 17th Floor Xinda Commerical Building No 318, Xian Xia Road Shanahai
● Tel : 86-21-6252-4291 ● Fax : 86-21-6278-4372
● e-mail : jkkimb@lgis.com

■ LG Industrial Systems Beijing Office China

● Address : 6F North B/D, EAS 21 XIAO YUN ROAD, Dong San Huan Bei Road, Chao Yang District, Beijing, China
● Tel : 86-10-6462-3259/4 ● Fax : 86-10-6462-3236
● e-mail : sclim@mx.cei.gov.cn

■ LG Industrial Systems Shanghai Office China

● Address : Room1705-1707, 17th Floor Xinda Commerical Building No 318, Xian Xia Road Shanahai, China
● Tel : 86-21-6278-4370 ● Fax : 86-21-6278-4301
● e-mail : ijkim1005@hanmail.net

■ LG Industrial Systems Guangzhou Office China

● Address : Room 303, 3F, Zheng Sheng Building, No 5-6, Tian He Bei Road, Guangzhou, China
● Tel : 86-20-8755-3410 ● Fax : 86-20-8755-3408
● e-mail : lgisgz@public1.guangzhou.gd.cn

■ LG Industrial Systems New Jersey Office USA

● Address : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey 07632 USA
● Tel : 1-201-816-2985 ● Fax : 1-201-816-2343
● e-mail : hskim@lgisusa.com

■ LG Industrial Systems Tokyo Office Japan

● Address : 16F, Higashi-Kan, Akasaka Twin Towers 17-22, 2-chome, Akasaka, Minato-ku Tokyo 107-0052, Japan
● Tel : 81-3-3582-9126 ● Fax : 81-3-3582-0062
● e-mail : snbaek@partner.lgis.co.jp

LG constantly endeavor to improve our products so that information in this catalog is subject to change without notice.