

Domae: the right solution for every home

Household
Miniature Circuit Breakers



Residential



Schneider
Electric

Domae, the offer adapted

1 Total safety

With the Domae offer, Schneider Electric guarantees the very best in quality for this entire product range (26 ISO 9001/ 2000 certified production and development sites world-wide).

What's more, because this range has been built to comply with European and international standards as well as Aenor requirements, you know you will be working in complete safety.



- > Designed according to the international standards (IEC 60898)
- > Certified by a notified body of reputation (VDE)
- > Manufactured by ISO 9001/2000 certified factories
- > Assured by Schneider Electric against fire or electrocution hazards caused by short-circuits, overload or faulty devices.




2 Simple to choose, easy to install

Domae makes life simple with this range of electrical products especially designed for the housing sector. You can rest assured that your switchboard will meet the requirements of IEC 60364 without changing any of your wiring habits.

- > Bi-stable lock for easy mousing
- > Large terminals with guards for secured connection
- > Disbo Extra enclosures along with Domae meet the specifications for wiring regulations
- > A comprehensive range of MCB's
- > Fully available from Schneider Electric official distribution
- > Dedicated packaging and identification for an easy selection



- Fingersafe terminals, screws for flat-headed or recessed head screw screwdrivers.



- Simple, fool-proof wiring.

to every home




3 Safe to use

Domae enclosures and switchgear have been designed to prevent electrical installation risks in the home. So you can be 100% sure that users will be protected against fire or electrocution hazards caused by short circuits, overloads or faulty devices.





4 A professional, good-looking design

Domae products can be easily identified by their new design



Domae products comply with Schneider Electric guiding system

- > A complete final distribution system along with Disbo Extra enclosures
- > For more details on Disbo Extra range offer refer to the brochure available with your distributors



- Easily identifiable circuits.



- A remarkable profile.

5 Always available

Domae stands for a simple and comprehensive range of 31 products. You will always find these products at your usual retailer outlet.

Perfect spectrum for domestic appliances

- > Current rating: 6, 10, 16, 20, 25, 32, 40A
- > C curve: suitable for household applications
- > Breaking capacity: 6 kA at 240/415 VAC as per IEC 60898
- > Operational voltage: 240/415 VAC
- > Limitation class: 3
- > 2 position handle: On/Off with I/O indicator
- > Clamping screw: screw head 5mm blade or PZ2 recessed
- > Terminal capacity: 25mm² max terminals with guards for rigid copper cables
- > Quality mark and approval VDE
- > Marking zone: 18 x 12mm user labels
- > Identification of the household range

Selection guide

Type	Rating I (A)	Reference	Characteristics width in 9 mm module
 Domae 1P Curve C	6	17044	2
	10	17045	
	16	17046	
	20	17047	
	25	17048	
	32	17049	
	40	17050	
 Domae 2P Curve C	6	17058	4
	10	17059	
	16	17060	
	20	17061	
	25	17062	
	32	17063	
	40	17064	
 Domae 3P Curve C	6	17078	6
	10	17079	
	16	17080	
	20	17081	
	25	17082	
	32	17083	
	40	17084	

Customer Care Center
920 011 101

Fax: +971 4 883 09 57

E-mail: ae-ccc-gulf@ae.schneider-electric.com

www.schneider-electric.com.sa

Schneider Electric Saudi Arabia

	Head Office	Riyadh Branch	Jeddah Branch	Al-Khobar Branch	OGP Branch
Address	PO Box 89249 Riyadh 11682	PO Box 89249 Riyadh 11682	PO Box 118132 Jeddah 21312	PO Box 3789 Al-Khobar 31952	PO Box 32044 Al-Khobar 31952
Tel.	01 265 15 15	01 291 28 77	02 697 77 23	03 896 09 10	03 814 71 77
Fax.	01 265 18 60	01 472 53 35	02 697 33 08	03 896 08 20	03 814 71 79
	Al-Madinah Office	Tabuk Office	Yanbu Office	Qassim Office	Abha/Khamis Office
Tel.	04 827 50 05	04 424 59 33	04 393 11 93	06 326 23 54	07 220 15 18
Fax.	04 822 36 56	04 424 16 33	04 392 66 02	06 327 05 48	07 237 19 17

As standards, specifications and designs change from time to time, please ask for confirmation of the information given in this publication